


Tapered roller bearing 343-332-B-TIMKEN - 343-332-B-TIMKEN

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/343-332-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF



| Bearing Dimensions | | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|--|-----------------------------|------|--|-----------------------------|--------------------------|-------|-------------|-------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e | Y | Dynamic ⁽¹⁾ C ₂ | Factors ⁽²⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | | N | | N | | | |
| 34.925 | 80.000 | 7.938 | 79500 | 0.27 | 1.25 | 23000 | 9600 | 2.14 | 82600 | 343 | 332-B |
| 1.3750 | 3.1496 | 0.3125 | 17900 | | | 4640 | 2170 | | 16100 | | |

| Bearing Dimensions | | | | | | Shaft | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|--|-----------------------------------|--|--|--|--|--|------------------|----------------|----------------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽³⁾ | Outer Ring Range D ₁ D ₂ | Flange Width C ₁ | Max Shaft File Radius R ⁽⁴⁾ | Sealing Shoulder Dia. d ₁ | Sealing Shoulder Dia. d ₂ | Sealing Shoulder Dia. D ₁ | Sealing Shoulder Dia. D ₂ | G ₁ | G ₂ | C ₃ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | lbs. |
| 79.400 | 17.800 | -4.4 | 84.000 | 4.700 | 3.5 | 81.5 | 88.0 | 77.0 | 77.0 | 26.5 | 13.0 | 0.0076 | 6.86 |
| 0.8020 | 0.7018 | -0.25 | 3.3000 | 0.1875 | 0.14 | 1.62 | 1.88 | 3.03 | 3.03 | | | | 1.21 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | TIMKEN |
| N° Ean13 | 3663952336084 |
| Inside diameter | 34.925 mm |
| Inside diameter | 1 3/8" inch |
| Outside diameter | 80 mm |
| Outside diameter | 3.15" inch |
| Thickness | 7.938 mm |
| Thickness | 5/16" inch |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE