

Tapered roller bearing 32056X-TIMKEN - 32056X-TIMKEN

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/32056x-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • IsoClass

IsoClass

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽³⁾ C ₂	Factor ⁽⁴⁾ K	Static C ₀	Assembly Inner/Outer		
mm	mm	mm	N		N	N	N			
in.	in.	in.	lbf		lbf	lbf	lbf			
280.000	420.000	87.000	1380000	0.14	257000	200000	1.27	2620000	32056X	
11.0236	16.5354	3.4252	309500		60200	63000		5900000		

Mounting Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER Co. a ⁽¹⁾	Max Shaft Fillet Radius R ⁽²⁾	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ⁽³⁾	Backing Shoulder Dia. D _s	Backing Shoulder Dia. D ₂	A ₁ ⁽⁴⁾	A ₂ ⁽⁵⁾	G ₁	G ₂	C ₃	kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	lb.	
87.000	165.000	3.8	3.8	262.3	216.0	4.0	402.0	206.1	11.3	4.1	100.1	175.3	0.1812	60.30
3.4252	6.5000	0.15	0.25	11.89	12.38	0.16	15.83	15.20	0.44	0.16			0.819	86.81

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952354200
Inside diameter	280 mm
Outside diameter	420 mm
Thickness	87 mm
Packaging	1

contact@123bearing.ca
+1(646) 712 9672
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE