


Drawn cup roller bearing YB2016-IKO - YB2016-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/drawn-cup/yb2016-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number												
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g				
31.750 (1 1/4)	—	—	—	—	—	—	—	—	YB 2016	57			
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	t	Shaft dia. mm	Housing bore dia. mm	C_1	C_2	C_3	N	N	rpm	IRB 1616	
31.750 (1 1/4)	38.100 (1 1/2)	25.40 (1.000)	—	31.750 (1.250)	31.734 (1.249)	38.114 (1.501)	38.089 (1.500)	40	900	100 000	4 500	IRB 1616	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952362359
Inside diameter	31.75 mm
Outside diameter	38.1 mm
Thickness	25.4 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE