

Tapered roller bearing NA82587-82932D-TIMKEN - NA82587-82932D-TIMKEN

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/na82587-82932d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TNA

TYPE TNA

| Bearing Dimensions | | | | Load Ratings | | | | | | | | | |
|--------------------|---------|---------|---------------------------|------------------------|--------|------------------------|----------------|------------------------|--------|------------------------|--------|------|--|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic ⁽¹⁾ | | Factors ⁽²⁾ | | Dynamic ⁽¹⁾ | | Factors ⁽²⁾ | | K | |
| mm | mm | mm | mm | C ₁₀ | N | Y ₁ | Y ₂ | C ₁₀ | N | C ₉₀ | N | | |
| 149.225 | 236.538 | 131.762 | 106.362 | 307000 | 252000 | 0.64 | 1.53 | 2.27 | 134000 | 101000 | 232000 | 1.52 | |
| 5.8750 | 9.3125 | 5.1875 | 4.1875 | 382000 | 312000 | | | | 30000 | 22700 | 52000 | | |

| Part Number | | Shaft | | | | Housing | | | | Pin | Bearing Weight |
|-------------|--------|--|--------------------------------------|--|--------------------------------------|----------------|----------------|----------------|----------|--------------|----------------|
| Inner | Outer | Max Shaft Fillet Radius R _f | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r _h | Backing Shoulder Dia. D _s | K _a | K _b | K _c | Pin | | |
| NA82587 | 82932D | mm 3.5 | mm 100.0 | mm 1.5 | mm 226.0 | mm — | mm — | mm — | mm — | kg 18.82 | |
| | | in. 0.14 | in. 3.94 | in. 0.06 | in. 8.90 | in. — | in. — | in. — | in. — | lb. 41.73 | |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | TIMKEN |
| N° Ean13 | 3663952374277 |
| Inside diameter | 149.225 mm |
| Outside diameter | 236.538 mm |
| Thickness | 131.762 mm |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE