


Needle roller bearing RNA4900-U-IKO - RNA4900-U-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/rna4900-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_a (1)
14	---	RNA 4900U	---	---	16.3	14	22	13	0.3
Standard rounding dimension D_s Max. mm	N	N	N	N					
Basic dynamic load rating C Max. mm	8 080	8 490	8 490	14 000					
Basic static load rating C_0 Max. mm	N	N	N	N					
Allowable rotational speed (1) rpm	N	N	N	N					

Notes: (1) Minimum allowable value of chamfer dimension r . Allowable rotational speed applies to grease lubrication. The outer ring has an oil groove and an oil hole.
Remarks: 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952378787
Inside diameter	14 mm
Outside diameter	22 mm
Thickness	13 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE