

Needle roller bearing RNA6916-UU-IKO - RNA6916-UU-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/rna6916-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
90	—	—	RNA6916UU	—	1 010	90	110	54	1
Standard mounting dimension D_s Max. mm									
	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (2)						
105	132 000	317 000	2 000						

Notes: (1) Minimum allowable value of chamfer dimension r . Allowable rotational speed applies to grease lubrication.
(2) The outer ring has an oil groove and an oil hole.
Remarks: 1. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379708
Inside diameter	90 mm
Outside diameter	110 mm
Thickness	54 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE