

## Needle roller bearing NA6902-U-IKO - NA6902-U-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/na6902-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
<b>15</b>	—	—	—	—	<b>NA 6902U</b>	62.5	15	28	23	24

$r_s$ min ( <sup>1)</sup> )	$F_w$	Standard mounting dimensions mm			Basic static load rating $C_0$ N	Basic dynamic load rating $C_1$ N	Allowable rotational speed( <sup>2)</sup> ) rpm	Assembled inner ring
		Min.	Max.	$d_s$				
0.3	20	17	19	26	18 500	27 100	9 500	LRTZ 152024

Note(<sup>1</sup>) Minimum allowable value of chamfer dimension r  
 Note(<sup>2</sup>) Allowable rotational speed applies to grease lubrication.  
 Remark: This outer ring has an oil groove and an oil hole.  
 1. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381138
Inside diameter	15 mm
Outside diameter	28 mm
Thickness	24 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE