

Needle roller bearing NA6904-U-IKO - NA6904-U-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/na6904-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
20	—	—	—	—	NA 6904U	137	20	37	30	31

r _s min ⁽¹⁾	F _w	Standard mounting dimensions mm			Basic static load rating C ₀ N	Basic dynamic load rating C ₁₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		Min.	Max.	Max.				
0.3	25	22	24	35	33 000	44 600	7 500	LRTZ 202531

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381244
Inside diameter	20 mm
Outside diameter	37 mm
Thickness	31 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE