


## Needle roller bearing NA69-22-U-IKO - NA69-22-U-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/na69-22-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
<b>22</b>	—	—	—	—	<b>NA 69/22U</b>	153	22	39	30	31

$r_s$ min mm	$F_w$	Standard mounting dimensions mm			Basic static load rating $C_0$ N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		Min.	Max.	Max.				
0.3	28	24	27	37	33 800	52 000	7 000	LRTZ 222831

Note<sup>(1)</sup> Minimum allowable value of diameter dimension  $r$   
 (2) Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 1. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381282
Inside diameter	22 mm
Outside diameter	39 mm
Thickness	31 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE