

Needle roller bearing NA4907-U-IKO - NA4907-U-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/na4907-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|------------------|-----------------------|-----------------|----------------|---------------|---------------------|---------------------------|----|----|----|
| | With two seals | With one seal | With two seals | With one seal | | d | D | C | B |
| 35 | — | NA 4907U | — | — | 179 | 35 | 55 | 20 | 21 |

| r _s min (¹) | F _w | Standard mounting dimensions mm | | | | Basic static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring |
|--|----------------|------------------------------------|------|----------------|---------------------|---|--|----------------------|
| | | Min. | Max. | d _s | D _s Max. | | | |
| 0.6 | 42 | 39 | 41 | 51 | 30 100 | 46 300 | 4 500 | LRTZ 354221 |

Note(1) Minimum allowable value of shaft diameter r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952381466 |
| Inside diameter | 35 mm |
| Outside diameter | 55 mm |
| Thickness | 21 mm |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE