

Needle roller bearing NA4909-U-IKO - NA4909-U-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/na4909-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
45	—	NA 4909U	—	—	290	45	68	22	23

r _s min ⁽¹⁾ mm	F _w	Standard mounting dimensions mm		Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		d _s Min.	d _s Max.			
0.6	52	49	51	38 900	3 500	LRTZ 455223

Notes: (1) Minimum allowable value of diameter dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381541
Inside diameter	45 mm
Outside diameter	68 mm
Thickness	23 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE