

Needle roller bearing NA4910-U-IKO - NA4910-U-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/na4910-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
50	—	NA 4910U	—	—	295	50	72	22	23

r_s min (1)	F_w	Standard mounting dimensions mm			Basic static load rating C_0 N	Allowable rotational speed(2) rpm	Assembled inner ring	
		Min.	Max.	D_s Max.				
0.6	58	54	57	68	41 300	71 100	3 500	LRTZ 505823

Note(1) Minimum allowable value of chamfer dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: The outer ring has an oil groove and an oil hole.
 1. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381589
Inside diameter	50 mm
Outside diameter	72 mm
Thickness	23 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE