

## Needle roller bearing NA4911-U-IKO - NA4911-U-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/na4911-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
<b>55</b>	—	<b>NA 4911 U</b>	—	—	415	55	80	25	26

r <sub>s</sub> min <sup>(1)</sup> F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub>	Basic dynamic load rating C <sub>10</sub>	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
	Min.	Max.	Max.					
1	63	60	61	75	52 200	85 700	3 000	LRTZ 556326

Note(1) Minimum allowable value of chamfer dimension r  
 (2) Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381626
Inside diameter	55 mm
Outside diameter	80 mm
Thickness	26 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE