

## Needle roller bearing NA6914-U-IKO - NA6914-U-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/na6914-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
<b>70</b>	—	—	—	—	<b>NA 6914U</b>	1 400	70	100	54	55

r <sub>s</sub> min (1)	F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		d <sub>s</sub> Min.	d <sub>s</sub> Max.	D <sub>s</sub> Max.				
1	80	75	78	95	124 000	281 000	2 500	LRTZ 708055

Note(1) Minimum allowable value of diameter dimension r  
 (2) Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 1. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381756
Inside diameter	70 mm
Outside diameter	100 mm
Thickness	55 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE