

## Needle roller bearing NA6914-UU-IKO - NA6914-UU-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/na6914-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.)	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$\beta$	d	D	C
<b>70</b>	—	—	<b>NA 6914UU</b>	—	1 400	70	100	54	55

$r_s$ min	$F_w$	Standard mounting dimensions mm			Basic static load rating $C_0$	Basic dynamic load rating N	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring
		Min.	Max.	$d_s$				
1	80	75	78	95	124 000	281 000	2 500	LRTZ 709055

Notes: (1) Minimum allowable value of diameter dimension  $r$   
 (2) Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381763
Inside diameter	70 mm
Outside diameter	100 mm
Thickness	55 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE