

## Needle roller bearing BRI183020-UU-IKO - BRI183020-UU-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/bri183020-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
<b>28.575</b> (1.125)	<b>BRI 183020 UU</b>		211	28.575 (1.125)	47.625 (1.875)	31.750 (1.250)	32.000	

  

$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating $C_0$	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring LRBZ 182220 B
	Min.	Max.	Max. as max. <sup>(*)</sup>				
34.925 (1.375)	33.5	33.9	42.4	38 500	60 000	5 500	LRBZ 182220 B

Notes: (\*) Minimum allowable value of chamfer dimension r  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382586
Inside diameter	28.575 mm
Outside diameter	47.625 mm
Thickness	31.75 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE