

Needle roller bearing BRI223520-UU-IKO - BRI223520-UU-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/bri223520-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | |
|----------------------------|-----------------------|---------------|---------------------|------------------------------|----------------|----------------|--------|--|
| | With two seals | With one seal | | d | D | C | B | |
| 34.925 (1 3/8) | BRI 223520 UU | | 275 | 34.925 (1 3/8) | 55.562 (2 1/8) | 31.750 (1 1/4) | 32.000 | |

| F _w | Standard mounting dimensions (mm) | | | Basic dynamic load rating C N | Basic static load rating C ₀ N | Allowable rotational speed ^(*) rpm | Assembled inner ring LRBZ 222620 B |
|----------------|-----------------------------------|------------------------|------------------------|-------------------------------------|---|--|---------------------------------------|
| | d _s Min. | d _s Max. | D _s Max. | | | | |
| 41.275 (1 5/8) | 40.2 | 40.2 | 48.3 | 44 800 | 70 900 | 4 500 | |

Notes: (*) Minimum allowable value of diameter dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952382623 |
| Inside diameter | 34.925 mm |
| Outside diameter | 55.562 mm |
| Thickness | 31.75 mm |
| Packaging | 1 |

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE