


## Needle roller bearing GBR142216-UU-IKO - GBR142216-UU-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/gbr142216-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>22.225</b> ( $\frac{9}{16}$ )	<b>GBR 142216 UU</b>		89.5	22.225 ( $\frac{9}{16}$ )	34.925 ( $1\frac{1}{8}$ )	25.400 (1)
Standard mounting dimensions mm		Ball/roller seal ring	Ball/roller diameter	Allowable rotational speed <sup>(*)</sup>		
$D_A$	$r$ as max	$C$	$C_0$	rpm		
30	0.6	28 600	40 100	3 500		

Notes: (\*) Minimum allowable value of diameter dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382890
Inside diameter	22.225 mm
Outside diameter	34.925 mm
Thickness	25.4 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE