

Needle roller bearing GBR223020-UU-IKO - GBR223020-UU-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/gbr223020-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
34.925 (1 3/8)	GBR 223020 UU		183	34.925 (1 3/8)	47.625 (1 7/8)	31.750 (1 1/4)
Standard mounting dimensions mm		Seal dynamic load rating C	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_A Max.	r as max (°)	N	N	rpm		
42.8	0.6	49 500	91 800	2 500		

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382968
Inside diameter	34.925 mm
Outside diameter	47.625 mm
Thickness	31.75 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE