


## Needle roller bearing GBR223020-U-IKO - GBR223020-U-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/gbr223020-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With 6/8e seal		$F_w$	$D$	$C$
<b>34.925</b> (1 3/8)	<b>GBR 223020 UU</b>		183	34.925 (1 3/8)	47.625 (1 7/8)	31.750 (1 1/4)
Standard mounting dimensions mm		Seal dynamic load rating $C$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_s$	$r$ as max	N	N	rpm		
42.8	0.6	49 500	91 800	2 500		

Notes: (\*) Minimum allowable value of diameter dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382975
Inside diameter	34.925 mm
Inside diameter	1 3/8" inch
Outside diameter	47.625 mm
Outside diameter	1 7/8" inch
Thickness	31.75 mm
Thickness	1 1/4" inch
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE