


## Needle roller bearing GBR1243920-U-IKO - GBR1243920-U-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/gbr1243920-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)					
	With two seals	With one seal		d	D	C			
<b>38.100</b> (1 1/2)	<b>GBR1 243920 U</b>		400	38.100 (1 1/2)	61.912 (2 1/2)	31.750 (1 1/4)			
B	F <sub>w</sub>	Standoff mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring		
		Min.	Max.					D <sub>s</sub> Max.	r <sub>as max</sub> <sup>(1)</sup>
32.000	47.625 (1 7/8)	43.3	45	56.2	1	61 100	121 000	1 700	<b>LRBZ 243020</b>

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383460
Inside diameter	38.1 mm
Outside diameter	61.912 mm
Thickness	31.75 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE