


Needle roller bearing TRU284530-UU-IKO - TRU284530-UU-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/tru284530-uu-iko>

IKO
ROLLER BEARINGS

Caged Roller Bearings [With Seal]
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r ⁽¹⁾	J
28	—	TRU 284530UU	173	28	45	30	0.3	31.5
E_w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n _{gr}					
39.5	28 700	43 800	8 000					

Notes: (1) Minimum allowable value of chamfer dimension r.
(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and NLU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386096
Inside diameter	28 mm
Outside diameter	45 mm
Thickness	30 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE