


Needle roller bearing TRU325230-UU-IKO - TRU325230-UU-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/tru325230-uu-iko>

IKO
ROLLER BEARINGS

Caged Roller Bearings **[With Seal]**
Full Complement Roller Bearings **[With Seal]**



Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r ⁽¹⁾ min	J
32	---	---	TRU 325230UU	260	32	52	30	0.6	38
E_w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n ₁ rpm						
46	N 29 800	N 44 200	5 000						

Notes: (1) Minimum allowable value of chamfer dimension r.
(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386102
Inside diameter	32 mm
Outside diameter	52 mm
Thickness	30 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE