


Needle roller bearing TRU456430-UU-IKO - TRU456430-UU-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/tru456430-uu-iko>

IKO
ROLLER BEARINGS

Caged Roller Bearings **[With Seal]**
Full Complement Roller Bearings **[With Seal]**



Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r ^(*) min	J
45	---	---	TRU 456430UU	295	45	64	30	0.6	50.5
E _w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n _g rpm						
	N	N	2 500						

Notes(*)
(*) Minimum allowable value of chamfer dimension r
(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386171
Inside diameter	45 mm
Outside diameter	64 mm
Thickness	30 mm
Weight	300 g
Packaging	1
Standard	No standard

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE