


Needle roller bearing TRU608945-UU-IKO - TRU608945-UU-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/tru608945-uu-iko>

IKO
ROLLER BEARINGS

Caged Roller Bearings [With Seal]
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r ⁽¹⁾	J
60	—	—	TRU 608945UU	880	60	89	45	1	69.5
E_w	N	N							
81.5	B8 100	152 000	3 000						

Notes: (1) Minimum allowable value of chamfer dimension r.
(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386249
Inside diameter	60 mm
Outside diameter	89 mm
Thickness	45 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE