

## Needle roller bearing NAU4919-UU-IKO - NAU4919-UU-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/nau4919-uu-iko>

**IKO**  
**ROLLER BEARINGS**

Caged Roller Bearings **[With Seal]**  
Full Complement Roller Bearings **[With Seal]**

Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r <sup>(1)</sup> min	J
95	---	<b>NAU 4919UU</b>	1 270	95	130	35	1.5	106
$E_w$	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed n <sub>2</sub> rpm					
120.5	B1 000	136 000	1 800					

Notes: (1) Minimum allowable value of chamfer dimension r.  
(\*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAU and TRU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386560
Inside diameter	95 mm
Outside diameter	130 mm
Thickness	35 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE