


Needle roller bearing NAS5020-ZZ-NR-IKO - NAS5020-ZZ-NR-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/nas5020-zz-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
100		NAS 5020ZZNR	4.05	100	150	155.4	67	66	54	6

f	c	r _s mm ⁽¹⁾	J	Basic dynamic load rating C N	Static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm
2.5	2.5	0.6	118	318 000	584 000	1 000

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386980
Inside diameter	100 mm
Inside diameter	3.937" inch
Outside diameter	150 mm
Outside diameter	5.906" inch
Thickness	67 mm
Thickness	2.638" inch
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE