


## Needle roller bearing NBX6040Z-IKO - NBX6040Z-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/nbx6040z-iko>

**IKO**

**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring  
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring



Identification number												
Shaft dia. mm	Mass (Ref.) g		With dust cover Mass (Ref.) g		Mass (Ref.) g		With dust cover Mass (Ref.) g					
60	---	---	---	---	---	---	---	---	<b>NBX 6040Z</b> 538			
Boundary dimensions mm												
$F_w$	$D$	$D_1$	$D_2$	$L$	$H$	$r_1$ min.	$d_f$	Basic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed <sup>(2)</sup> rpm		
60	72	85	86.5	40	17	1	60	47 500	64 600	103 000	224 000	4 000

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.

Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390529
Inside diameter	60 mm
Outside diameter	72 mm
Thickness	40 mm
Packaging	1
Standard	No standard

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE