

## Needle roller bearing NAXI1223-IKO - NAXI1223-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/naxi1223-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
12	<b>NAXI 1223</b>	55.5	—	—	—	—	12	24	28

  

Boundary dimensions mm				Bore diameter mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
D <sub>2</sub>	L	B	H			Radial	Radial		
25	23	16	9	6.5	8 230	9 190	11 100	9 500	LRT 71016

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390680
Inside diameter	12 mm
Outside diameter	24 mm
Thickness	23 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE