

# Needle roller bearing NBXI3532-IKO - NBXI3532-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/nbxi3532-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
35	---	---	---	<b>NBXI 3532</b>	286	---	35	52	60

  

Boundary dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring							
D <sub>2</sub>	L	B	H		Radial	Axial									
61	32	20	13	10	0.6	0.3	40	57	39	29 400	41 700	54 100	133 000	6 000	LRT 354020

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
 Remarks: 1. The outer ring has an oil groove and an oil hole.  
 2. Grease is not prepacked. Perform proper lubrication.

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390949
Inside diameter	35 mm
Outside diameter	52 mm
Thickness	32 mm
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE