

Needle roller bearing NBXI5040-IKO - NBXI5040-IKO

<https://www.123bearing.ca/bearing-housing/needle-roller-bearing/needle/nbxi5040-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
50	---	---	---	NBXI 5040	666	---	50	72	85

Boundary dimensions mm										Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRT 506025
D ₂	L	B	H	I ₁	r _{max}	r _{min}	d ₄	d ₅	Min.	Radial	Axial	Radial	Axial		
86.5	40	25.5	17	12	1	1	60	82	59	47 500	64 600	103 000	224 000	4 000	

Notes:
 (1) Minimum allowable value of chamfer dimension r.
 (2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
 Remarks:
 1. The outer ring has an oil groove and an oil hole.
 2. Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391069
Inside diameter	50 mm
Outside diameter	72 mm
Thickness	40 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE