


## GE Rod end SB115A-IKO - SB115A-IKO

<https://www.123bearing.ca/bearing-housing/rod-end/ge/sb115a-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree $\alpha$
			$d$	$D$	$B$	$C$	$d_k$	$r_1$ mm <sup>(1)</sup>	
115	<b>SB 115A</b>	10.3	115	180	98	85	165	1	5
Mounting dimensions mm		Dynamic load capacity $C_d$ N	Static load capacity $C_s$ N	$d_s$		$D_s$			
Min.	Max. <sup>(2)</sup>			Min.	Max.	Min.	Max.		
120.5	132.5	174.5	152	1 380 000	8 250 000				

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391564
Inside diameter	115 mm
Outside diameter	180 mm
Thickness	98 mm
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE