

## GE Rod end SB150A-IKO - SB150A-IKO

<https://www.123bearing.ca/bearing-housing/rod-end/ge/sb150a-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree $\alpha$	
			$d$	$D$	$B$	$C$	$d_k$ <sup>(1)</sup> $r_2$ mm		
150	<b>SB 150A</b>	17.0	150	220	120	105	205	1	5

Mounting dimensions mm				Dynamic load capacity $C_d$ N	Static load capacity $C_s$ N
$d_s$ Min.	$d_s$ Max. <sup>(2)</sup>	$D_s$ Min.	$D_s$ Max.		
155.5	166	214.5	189	2 110 000	12 700 000

Notes: <sup>(1)</sup> Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391625
Inside diameter	150 mm
Outside diameter	220 mm
Thickness	120 mm
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE