

GE Rod end GE90GS-2RS-IKO - GE90GS-2RS-IKO

<https://www.123bearing.ca/bearing-housing/rod-end/ge/ge90gs-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1	
90		GE 90GS-2RS	5.41	90	150	85	55	130	1	1	15	14	
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s									
d_s		D_s		N		N							
Min.	Max.(2)	Max.	Min.	N		N							
95.5	98	144.5	127	701 000		4 210 000							

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392486
Inside diameter	90 mm
Outside diameter	150 mm
Thickness	85 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE