

GE Rod end GE160GS-IKO - GE160GS-IKO

<https://www.123bearing.ca/bearing-housing/rod-end/ge/ge160gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm							Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d _s	r ₁ (1)	r ₂ (1)	α	α ₁	
160	GE 160GS		25.4	160	260	135	80	225	1	1.1	16	14	
Mounting dimensions mm			Dynamic load capacity C _d N	Static load capacity C _s N									
d _s		D _s											
Min.	Max.(2)	Max.	Min.										
165.5	180	253	221	1 770 000		10 600 000							

Notes(1)
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392585
Inside diameter	160 mm
Outside diameter	260 mm
Thickness	135 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE