

GE Rod end GE70EC-2RS-IKO - GE70EC-2RS-IKO

<https://www.123bearing.ca/bearing-housing/rod-end/ge/ge70ec-2rs-iko>



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d _k	r ₁ mm ⁽¹⁾	r ₂ mm ⁽¹⁾	α	α ₁
70	—	GE 70EC-2RS	1.54	70	105	49	40	92	1	1	—	4
Mounting dimensions mm		Dynamic load capacity C _D		Static load capacity C _S								
Min. Max. ⁽²⁾		Max. Min.		N		N						
75.5 77.5		99.5 91		361 000		902 000						

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
 Remark No oil hole is provided.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952393230
Inside diameter	70 mm
Outside diameter	105 mm
Thickness	49 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE