

Tapered roller bearing 33118-JR-JTEKT - 33118-JR-KOYO

<https://www.123bearing.ca/bearing-housing/roller-bearing/tapered/33118-jr-koyo>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.		
90	150	45	45	35	258	413	2 500	3 300	33118JR	

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
30E	35.4	102	100	140	130	144	7	10	2	2	0.40	1.51	0.83	3.13

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250250507
Inside diameter	90 mm
Outside diameter	150 mm
Thickness	45 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE