


## Cam follower CF24-1-V-IKO - CF24-1-V-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cf24-1-v-iko>



### CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



| Stud dia.<br>mm        | Identification number   |                             |                         |                             |                         |                             |                         |                             | CF-V        |                   |                           |                          |                         |                               |
|------------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|-------------------|---------------------------|--------------------------|-------------------------|-------------------------------|
|                        | Shield type             |                             |                         |                             | Sealed type             |                             |                         |                             | Mass (Ref.) |                   | D                         | C                        | d <sub>1</sub>          |                               |
|                        | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | g           |                   |                           |                          |                         |                               |
| 24                     | CF24-1-V                |                             |                         |                             |                         |                             |                         |                             | 1 140       | 72                | 29                        | 24                       |                         |                               |
| Boundary dimensions mm |                         |                             |                         |                             |                         |                             |                         |                             |             |                   |                           |                          |                         |                               |
| G                      | G <sub>1</sub>          | B                           | B <sub>1</sub>          | B <sub>2</sub>              | B <sub>3</sub>          | C <sub>1</sub>              | g <sub>1</sub>          | g <sub>2</sub>              | f           | Mounting diameter | Maximum tightening torque | Ball dynamic load rating | Ball static load rating | Maximum allowable static load |
| M24×1.5                | 25                      | 30.6                        | 80.1                    | 49.5                        | 11                      | 0.8                         | 8                       | 4                           | 1           | 40                | 215                       | 48 600                   | 92 000                  | 52 000                        |

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | IKO           |
| N° Ean13         | 3663952440682 |
| Inside diameter  | 24 mm         |
| Outside diameter | 72 mm         |
| Thickness        | 29 mm         |
| Packaging        | 1             |

[contact@123bearing.ca](mailto:contact@123bearing.ca)

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE