


Cam follower CF8-UUM-IKO - CF8-UUM-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cf8-uum-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UU

Stud dia. mm	Identification number				Mass (Ref.)								
	Shield type		Sealed type		g	D	C	d ₁	G				
B	With crowned outer ring	With cylindrical outer ring	With tapered outer ring	With cylindrical outer ring	28.5	19	11	B	M 8×1				
CF 8 UUM													
Boundary dimensions mm													
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _{max} ^(*)	f _{Min.} mm	Maximum ignoring stress N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N
10	12.2max	32.2max	20	—	0.6	*4	—	0.3	13	7.1	4 250	4 740	4 620

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441061
Inside diameter	8 mm
Outside diameter	19 mm
Thickness	11 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE