

Cam follower CF12-1-UUR-IKO - CF12-1-UUR-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cf12-1-uur-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage With Screwdriver Slot



Stud dia. mm	Identification number				Maxs (Ref.)				
	Shield type		Sealed type		g	D	C	d ₁	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
12	CF-12-1 UUR				105	32	14	12	M12×1.5

Boundary dimensions mm										Mounting diameter f Min. mm	Maximum ignoring stress N·m	Ball dynamic load rating C	Ball static load rating C ₀	Maximum allowable static load N
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _{smax} (°)	r _s					
13	15.2max	40.2max	25	6	0.6	6	3	0.6	21	21.9	7 910	9 790	9 790	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441306
Inside diameter	12 mm
Outside diameter	32 mm
Thickness	14 mm
Weight	98 g
Packaging	1
Standard	No standard

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE