

Cam follower CF20-UUR-IKO - CF20-UUR-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cf20-uur-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d ₁	G
	Shield type		Sealed type						
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
20			CF 20	UUR	480	52	24	20	M20×1.5

Boundary dimensions mm										Mounting torque N·m	Ball dynamic load rating C	Ball static load rating C ₀	Maximum allowable static load N
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max (°)	f Min. mm				
21	25.6max	66.1max	40.5	9	0.8	8	4	1	34	119	20 700	34 600	34 600

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441429
Inside diameter	20 mm
Outside diameter	52 mm
Thickness	24 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE