


Cam follower CF10-1-VBM-IKO - CF10-1-VBM-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cf10-1-vbm-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Hexagon Hole



CF-VB

Stud dia. mm	Identification number								Mass (Ref.)							
	Shield type				Sealed type				g	D	C	d ₁				
	With crowned outer ring		With cylindrical outer ring		With crowned outer ring		With cylindrical outer ring									
10	CF 10-1 VBM								61	26	12	10				
Boundary dimensions mm																
G	G ₁	B _{max}	B _{1max}	B ₂	B ₃	C ₁	g ₁	B ₂	H	(°)	f _{Min.}	Mounting dimension	Maximum tightening torque	Basic dynamic load rating	Basic static load rating	Maximum allowable static load
M10×1	12	13.2	36.2	23	—	0.6	—	—	4	0.3	16	14.7	9 570	14 500	8 650	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441955
Inside diameter	10 mm
Outside diameter	26 mm
Thickness	12 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE