


Cam follower CF10-BM-IKO - CF10-BM-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cf10-bm-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers **With Cage/With Hexagon Hole**



CF-B

Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d ₁	G
	Shield type		Sealed type						
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring					
10		CF 10 BM			45	22	12	10	M10×1

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum spinning torque N·m	Basic dynamic load rating C	Basic static load rating C ₀	Maximum allowable static load N
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	H	r _s mm					
12	13.2max	36.2max	23	—	0.6	—	—	4	0.3	16	14.7	5 430	6 890	6 890

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952442716
Inside diameter	10 mm
Outside diameter	22 mm
Thickness	12 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE