


Cam follower CFES6-BUUR-IKO - CFES6-BUUR-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cfes6-buur-iko>



CAM FOLLOWERS

Solid Eccentric Stud Type Cam Followers **With Cage/With Hexagon Hole**



CFES-BUUR

Stud dia. mm	Identification number								Mass (Ref.) g	D	C	d ₁				
	Shield type				Sealed type											
6	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	18.5	16	11	6				
CFES 6 BUUR																
Boundary dimensions mm																
G	G ₁	B	B ₁ max	B ₂ max	B ₃	C ₁	g ₁	g ₂	H	ε _{max} (°)	Mounting dimension f Min. mm	Maximum spinning torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
M 6×1	8	12.2	28.2	16	—	0.6	—	—	3	0.3	0.25	11	2.7	3 660	3 650	1 980

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952443386
Inside diameter	6 mm
Outside diameter	16 mm
Thickness	11 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE