

Cam follower CFE10-B-IKO - CFE10-B-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cfe10-b-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Hexagon Hole



CFE-B

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		Ø	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
13	CFE 10 B				49.5	22	12	13

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
G	B ₃	B _{max}	B _{1 max}	B ₂	C ₁	g ₁	G ₁	H _{max}	Eccentricity e						
M10×1.25	10.5	13.2	36.2	23	0.6	—	12.5	4	0.3	0.4	16	13.8	5 430	6 890	6 890

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459398
Inside diameter	13 mm
Outside diameter	22 mm
Thickness	12 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE