


Cam follower CFE24-1-BUUR-IKO - CFE24-1-BUUR-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cfe24-1-buur-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers | With Cage | With Hexagon Hole



Outside diameter of outer ring mm	Identification number				Mass (Ref.)				
	Shield type		Sealed type		Ø	D	C	d _e	
33	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					1 220
	CFE 24-1 BUUR								

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
G	B ₃	B _{max}	B _{1 max}	B ₂	C ₁	G ₁	H	H _{max}	ε						
M24×1.5	25.5	30.6	80.1	49.5	0.8	8	24	12	1	0.8	40	215	30 500	52 600	52 000

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952456256
Inside diameter	33 mm
Outside diameter	72 mm
Thickness	29 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE