


Cam follower CFE30-BUUR-IKO - CFE30-BUUR-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cfe30-buur-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Hexagon Hole



Outside diameter of outer ring mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
41	CFE 30 BUUR						2 030	80	35	41

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
G	B ₃	B _{max}	B _{1 max}	B ₂	C ₁	G ₁	H	H _{1 max}	Excentricity e						
M30×1.5	32.5	37	100	63	1	8	30.5	17	1	1.5	49	438	45 400	85 100	85 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459626
Inside diameter	41 mm
Outside diameter	80 mm
Thickness	35 mm
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE