


Cam follower CFE20-UU-IKO - CFE20-UU-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cfe20-uu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			ø	D	C	d ₂
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 20 UU					
27							500	52	24	27

Boundary dimensions mm										Essentiality g	Mounting dimension f mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G	B ₃	B max	B ₁ max	B ₂	C ₁	g ₁	G ₁	(1) r _{max}	e						
M20×1.5	19.5	25.6	66.1	40.5	0.8	8	21	1	0.8	34	119	20 700	34 600	34 600	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460066
Inside diameter	27 mm
Outside diameter	52 mm
Thickness	24 mm
Weight	500 g
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE