

Cam follower CFE24-1-VB-IKO - CFE24-1-VB-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cfe24-1-vb-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



Outside diameter of eccentric collar mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
33	CFE 24-1 VB						1 220	72	29	33

Boundary dimensions mm										
G	B ₃	B ₁ max	B ₂ max	B ₂	C ₁	G ₁	H	H _{max} (¹)	f mm	Mounting dimension g
M24×1.5	25.5	30.6	80.1	49.5	0.8	8	24	12	1	0.8

Mounting dimension f mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
40	215	46 600	92 000	52 000

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460738
Inside diameter	33 mm
Outside diameter	72 mm
Thickness	29 mm
Weight	1220 g
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE