

Cam follower CFE18-VUUR-IKO - CFE18-VUUR-IKO

<https://www.123bearing.ca/bearing-housing/deep-groove-bearing/cam-follower/cfe18-vuur-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
24	CFE 18		VUUR		285	40	20	24

Boundary dimensions mm														
G	B ₃	B _{max}	B ₁ _{max}	B ₂	C ₁	g ₁	G ₁	r ₁ ^(*)	Eccentricity E	Mounting diameter f Min.	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M18 X 1.5	17.5	21.6	58.1	36.5	0.8	6	19	1	0.8	29	86.2	25 300	51 300	31 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461155
Inside diameter	24 mm
Outside diameter	40 mm
Thickness	20 mm
Weight	285 g
Packaging	1

contact@123bearing.ca

+1(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE